

P-DAQ SQL SERVER UPDATE

The following outlines the procedures necessary to configure P-DAQ to use SQL Server and to convert the Access databases to SQL databases.

Create SQL Server Database on P-DAQ Server.

- Install Microsoft SQL Server 2000 on P-DAQ Server.
- Execute “Start...Programs...Microsoft SQL Server...Query Analyzer”.
- Open “PDAQ\Shared\Database\PDAQ6.SQL”.
- Execute SQL script to create **PDAQ** database.
- Set permissions for P-DAQ presses and clients.
- Insure that “DataSync” is terminated at all presses.
- Insure that the P-DAQ client modules are not being used.
- Rename “PDAQ\Shared\Database” to “PDAQ\Shared\DatabaseOld”.
- Execute “Start...Programs...Microsoft SQL Server...Import and Export Data”.
- Select Source = Microsoft Access = “PDAQ\Shared\DatabaseOld\Remote.mdb”.
- Select Destination = “PDAQ” database.
- Select ALL tables. Un-select ALL Queries.
- Continue with import.
- Execute “Start...Programs...Microsoft SQL Server...Import and Export Data”.
- Select Source = Microsoft Access = “PDAQ\Shared\DatabaseOld\Stats.mdb”.
- Select Destination = “PDAQ” database.
- Select ALL tables. Un-select ALL Queries.
- Continue with import.
- Edit “PDAQ\Shared\System.ini” file.
- Last line should read “DBTYTPE = SQL”. If it is commented out, remove apostrophe.
- Delete “PDAQ\Shared\DatabaseOld\Pressman.mdb”.

Press Update

- Create ODBC Data Source Name (DSN) called **PDAQ** for new PDAQ SQL Server database.
- Edit “Program Files\PDAQ\System.ini” file.
- Last line should read “DBTYTPE = SQL”. If commented out, remove apostrophe.
- Programs that require access to the P-DAQ server will not work yet.

Client Update

- Create ODBC Data Source Name (DSN) called **PDAQ** for new PDAQ SQL Server database.
- Edit "Program Files\PDAQ-Client\System.ini" file.
- Last line should read "DBTYTPE = SQL". If commented out, remove apostrophe.
- Programs that require access to the P-DAQ server will not work yet..

Server Update

- Ensure that all presses have been updated before proceeding.
- Rename "PDAQ\Shared\DatabaseOld" to "PDAQ\Shared\Database"
- Re-Start "DataSync" at all presses
- P-DAQ client module may now be used.